

KEN BEDPAN WASHER DISINFECTOR 736

Intelligent Disinfection

CLEAN, LEAN & GREEN

- ✓ Total disinfection
- ✓ Easy service access
- ✓ Complies with 15883

The BWD 736 has been developed for hospitals, special wards and nursing homes. It is useful for washing and disinfection of bedpans, urine bottles, washing bowls, suction glasses and similar utensils.

The machine has a small compact design and it leaves a small physical footprint, but still offers a large capacity. Furthermore, the BWD 736 is developed to be environmentally optimised with a low consumption of energy, water and detergents, which leads to low operational costs.

The BWD 736 is easy to operate by touch panel with icons showing all relevant information of the program needed by the operators.

The machine is functional as wall-mounted, but it can be floor-mounted with a plinth.

The different varieties of bedpan holders take all types of bedpans. The capacity of the BWD 736 is three bedpans or one bedpan and three urinal bottles per cycle.

A special utensils basket is available for washing kidney bowls and other small items.

All data from the BWD 736 are fully exchangeable with common computer systems.





HEALTHCARE



All KEN machines are in conformity with present EU directives, and all the hospital machines have been constructed in accordance with EN ISO 15883.

	Description	Values
Advantages:	Outer dimensions with/without plinth	H: 1740/1540 x W: 600 x D: 460 mm
Environment	Operative chamber dimensions	H: 500 x W: 485 x D: 370 mm
Low energy costs	Weight with plinth/without plinth	110 / 100 kg
Low water consumption	Integrated combi tank	12 L
	Built in detergent cabinet	Room for 2 x 5 L cans
Low chemical usage	Capacity, alternatively-	1 bedpan + 3 urine bottles OR
Low noise level User-friendliness		3 bedpans (2 with urine) OR 3 washing bowls OR 1 utensil basket OR 1 suction bottle OR
Easy to use icons		1 bucket
Quick-start - automatic closing	Bedpan program	Appr. 6 min
Door suitable as slopsink - bedpan	Sealing class	IP 21 (not rinse-proof)
emptied automatically	Water connections	Cold: 3/4" G (poss. 1/2" pipe), press.: 200-
Operated manually or automatically by		800kPa, temp.: 5-30°C, hardness: 0-3°dH
means of a foot pedal		Hot: 3/4" G (poss. 1/2" pipe), press.: 200-800kPa, temp.: 5-30°C, hardness: 0-3°dH
Hygiene safety	Sound level	Appr. 50 dB (A)
	Water consumption per phase	See technical manual
EN 62366 testedEN ISO 15883-1-3-5	Power supply options	3N x 200 - 440V AC 50/60Hz +PE+(N) (Single phase available)
Disinfection guarantee	Heating elements in combitank	6 kW / 9 kW
Ao value programmable from 60 - 3000	Programs available	5 standard + 1 optional
	Drain, S or P water trap	Inner ø90 mm, outer ø110 mm

Clean, Lean & Green







KEN HYGIENE SYSTEMS A/S © • Technical information and misprint are subject to alterations without notice.MEJ 08-22